Data Sheet
Fujitsu PRIMERGY RX300 S7 Dual socket 2 U rack server

The versatile 2U powerhouse

The PRIMERGY RX Rack Server family is the perfect platform to form dynamic infrastructures for your business processes today and in the coming decade. You will thus benefit several times over from our recognized experience in optimized data center technology and our innovative strength in developing energy-efficient and cost/performance-optimized rack systems for universal use. PRIMERGY rack servers, built upon industry standards, focus from a functional viewpoint on core features: energy efficiency, reliability, optimized for virtualization, ease of operation and maintenance, flexibility for your future. And thus they notably meet your requirements for outstanding cost efficiency. Optimal operating costs and long-term usability comply with the IT quality required by your customers. Our responsibility goes way beyond the hardware as our tailor-made service packages mean that you can rely on the best support for your IT during its whole lifecycle.

PRIMERGY RX300 S7

The Fujitsu PRIMERGY RX300 S7 is a dual socket rack server, focusing on versatility and scalability. The new modular concept supports excellent expandability with up to 16 hard disk drives, up to 7 PCIe Gen 3 cards and up to 768GB RAM, all in one single 2U rack housing. Furthermore, the new Intel® Xeon® E5 product family delivers the top performance to ensure today's demand while being prepared for future requirements thanks to the upgrade kits as well as the cost-saving Modular LAN options. Thanks to the power supply units with 94% efficiency and the new power management this will result in lower operational costs. This 2U power house is the right choice for all types of business applications and consolidations.

Features and Benefits

Main Features	Benefits
Meet today's demand and be prepared for future requirements	
■ Intel Xeon E5-2600 product family with up to 8 core processors and Turbo Boost 2.0	■ Increased performance of up to 80% compared to the previous generation ■ Optimized for business applications, cloud and virtualization
Lifecycle investment protection	
■ Expanded scalability of up to 24 DIMMs with 768 GB memory, up to 16 hard disk drives and 7 PCIe slots Gen3	■ Maximum scalability to meet future demand
■ New modular concept for the base unit as well as a choice for LAN controller, RAID controller and power supplies	■ Individual and cost-saving configuration of the server according to the need of today with upgrade option to meet the demand of tomorrow
■ Upgrade kits for hard disk drives, backup devices as well as LTO drives	■ Upgrade kits save budget as the system can be upgraded when the company grows and thus protect the investment ■ Ability to protect the data by integrating LTO drives
Cost efficient operations	
■ Simplified power management with profiles for 'minimum power' and 'low-noise'	■ Simplified and comprehensive power management that results with the high efficient power supplies in significant savings
■ 2 hot-plug PSU with 94% efficiency (80Plus platinum)	
■ Fujitsu ServerView Suite offers tools for installation and deployment, permanent status monitoring and control. A wide range of integration packs allow a seamless and easy integration in widely-used enterprise management systems	■ Fujitsu ServerView Suite provides all the functions for fail-safe, flexible and automated 24x7 server operations and improves end-user productivity via intelligent and innovative system management solutions.

Technical details

PRIMERGY RX300 S7		
Housing types	Rack	Rack
Storage drive architecture	6x 3.5-inch SAS/SATA	max. 16x 2.5-inch SAS/SATA
Power supply	Hot-plug	Hot-plug
Mainboard		
Mainboard type	D2939	
Chipset	Intel® C600 (Intel® Patsburg A)	
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2600 product family	
Processor	Intel® Xeon® processor E5-2603 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1066 MHz, 80 W)	
	Intel® Xeon® processor E5-2609 (4C/4T, 2.40 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1066 MHz, 80 W)	
	Intel® Xeon® processor E5-2620 (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2630 (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2630L (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 60 W)	
	Intel® Xeon® processor E5-2637 (2C/4T, 3.00 GHz, TLC: 5 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 80 W)	
	Intel® Xeon® processor E5-2640 (6C/12T, 2.50 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2643 (4C/8T, 3.30 GHz, TLC: 10 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2650 (8C/16T, 2.00 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 95 W)	
	Intel® Xeon® processor E5-2650L (8C/16T, 1.80 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 70 W)	
	Intel® Xeon® processor E5-2660 (8C/16T, 2.20 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 95 W)	
	Intel® Xeon® processor E5-2665 (8C/16T, 2.40 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 115 W)	
	Intel® Xeon® processor E5-2667 (6C/12T, 2.90 GHz, TLC: 15 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2670 (8C/16T, 2.60 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 115 W)	
	Intel® Xeon® processor E5-2680 (8C/16T, 2.70 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2687W (8C/16T, 3.10 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 150 W)	
	Intel® Xeon® processor E5-2690 (8C/16T, 2.90 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 135 W)	
Memory slots	24 (12 DIMMs per CPU, 4 channels with 3 slots per channel)	
Memory slot type	DIMM (DDR3)	
Memory capacity (min. - max.)	2 GB - 768 GB	
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Rank sparing memory support Memory Mirroring support (as soon as released)	

Memory notes	Max. 8 memory modules/CPU with UDIMM (low voltage or standard) OR quad-rank RDIMM; max. 12 memory modules/CPU with single or dual-rank RDIMM or single, dual-rank or quad-rank Load-Reduced (LR) DIMM. Memory Mirroring with identical modules in both channel pairs of a bank (4 modules per bank), Rank sparing or Performance Mode with identical modules in all four channels (4 modules per bank).
Memory options	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM
	16 GB (1 module(s) 16 GB) DDR3 LR LV, registered, ECC, 1333 MHz, PC3-10600, LRDIMM
	16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM
	32 GB (1 module(s) 32 GB) DDR3 LR LV, registered, ECC, 1333 MHz, PC3-10600, LRDIMM
Memory options	2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM
	4 GB (1 module(s) 4 GB) DDR3 LV, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM
Interfaces	
USB ports	10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x uSSD)
Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
LAN / Ethernet	2 x Gbit/s Ethernet (RJ45) with upgrade options for additional 2x1 Gbit/s (RJ45), 4x 1 Gbit/s (RJ45) or 2x 10 Gbit/s (SFP+)
Service LAN (RJ45)	1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller Front management LAN port as option
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Onboard or integrated Controller	
RAID controller	4 port for internal 3G SATA and SAS (as upgrade option "Patsburg B") for HDDs with RAID 0/1/10 or SAS LTO device (Intel C600) additional RAID controller options are described under Components RAID controller
SATA Controller	Intel® C600, 1 x SATA channel for ODD
LAN Controller	Intel® Ethernet Controller I350, 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration), Modular integrated on-board LAN offers upgrade options for additional 2x1 Gbit/s , 4x 1 Gbit/s or 2x 10 Gbit/s. PXE-Boot via LAN from PXE server, iSCSI boot (also diskless)
Remote Management Controller	Integrated Remote Management Controller (iRMC S3, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)
Slots	
PCI-Express 3.0 x8	5 x Low profile
PCI-Express 3.0 x16	2 x Low profile (2nd processor required)
Slot Notes	One PCIe Gen3 x8 slot may be occupied with a Modular integrated on-board LAN controller if configured. One PCIe Gen3 x8 slot may be occupied with a Modular RAID controller if configured. Important: 5 PCIe x8 slots are supported with the first processor. 7 PCIe slots (including 2 PCIe x16) are supported with two processors.
Drive bays	
Storage drive bays	2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 6 x 3.5)

Drive bays		
Accessible drive bays	1 x 5.25/0.5-inch for ODD 1 x 5.25/1.6-inch for ODD or backup devices 1 x 5.25/0.5-inch for Local Service Display	
Notes accessible drives	All possible options described in relevant system configurator.	
Drive bays (Base unit specific)		
Storage drive bays	6 x 3.5-inch hot-plug SAS/SATA	2.5-inch expandable x 2.5-inch hot-plug SAS/SATA
Storage drive bay configuration	max. 6x3.5"	max. 16x2.5"
Optional accessible drives	1x 3.5/1.6-inch bay for backup devices (occupies 2x 3.5-inch HDD)	LTO 5.25" or DAT/RDX 3.5" possible
General system information		
Number of fans	5	
Fan configuration	redundant / hot-plug	
Fan notes	4+1 redundant	
Operating panel		
Operating buttons	On/off switch Reset button NMI button ID button	
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)	
Service display	Optional: ServerView Local Service Display (LSD)	
BIOS		
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support	

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows HPC Server® 2008 R2 Suite
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Web Server 2008
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
	Citrix® XenServer®
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management

Standard	ServerView Suite - Deploy SV Installation Manager SV Scripting Toolkit SV Deployment Manager (30-day trial version) ServerView Suite - Control SV Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) SV Performance Management SV Power Management SV RAID Manager ServerView Suite - Maintain SV Remote Management (iRMC) SV Update Management (BIOS, Firmware, Windows Drives and SV Agents) SV Asset Management SV Online Diagnostics ServerView Suite - Integrate SV Integration packs e.g. for Microsoft System Center, Nagios, HP, SIM, HP NNM, IBM Tivoli, Altiris Deployment Solutions and others

Server Management	
Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage ServerView Suite - Dynamize SV Virtual-IO Manager (VIOM) SV Resource Orchestrator Virtual Edition (ROR VE) SV Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies for ServerView Suite software Products see dedicated Product Data sheets.
Dimensions / Weight	
Rack (W x D x H)	482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
Mounting Depth Rack	735 mm
Height Unit Rack	2 U
19" rackmount	Yes
Weight	up to 25 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option
Environmental	
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Low noise mode: 25 dB(A) min, 29 dB(A) max (idle) / 27 dB(A) min, 32 dB(A) max (operating) Performance mode: 48 dB(A) (idle) / 48 dB(A) min, 68 dB(A) max (operating)
Sound power (LWAd; 1B = 10dB)	Low noise mode: 4.1 B min, 4.5 max (idle) / 4.1 B min, 4.9 B max (operating) Performance mode: 6.5 B (idle) / 6.5 B min, 8.2 B max (operating)
Noise notes / description	Noise emissions and operation modes depend on system configuration.
Electrical values	
Power supply configuration	1-2x 450W/800W hot-plug power supply
Max. output of single power supply	450/800 W (94% efficiency)
Power supply efficiency	94 % (80 PLUS platinum)
Hot-plug power supply output	450/800 W (94% efficiency)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	8.2 A (100 V) / 3.3 A (240 V)
Rated current in basic configuration	100 V - 240 V / TBD
Active power (min. configuration)	53 W
Active power (max. configuration)	830 W
Apparent power (max. configuration)	873 VA
Heat emission	2988.0 kJ/h (2832.1 BTU/h)
Power Supply Notes	Power Safeguard adapts system performance in case the wattage exceeds supply limits.
Compliance	
Germany	GS
Europe	CE Class A *
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)

Compliance	
Japan	VCCI
China	CCC (planned) CCC (depending on configuration)
Australia/New Zealand	C-Tick
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks	
	SSD SATA, 6 Gb/s, 400 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 400 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 200 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 100 GB, SLC, hot-plug, 2.5-inch, enterprise
	PCIe SSD, 785 GB, MLC, Flash drive
	PCIe SSD, 1.2 TB, MLC, Flash drive
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 6 Gb/s, 3 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise

Backup Drives	
	DDS Gen5 (for 3.5-inch HDD bay), 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen5 3.5", 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
	LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
	LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

SCSI / SAS Controller	SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe Gen2 x8
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, LSI RAID Ctrl SAS 6G 1GB LSI, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int. RAID level: 0, 1, 10, No BBU support (based on LSI SAS2008)
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Emulex LPe12002 MMF LC-style
Communication, Network	Converged Network Adapter 2 x 10 Gbit/s PCIe x8 (Emulex)
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x1 (Intel®)
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x4 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe x8 (Fujitsu)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe x4 (Fujitsu)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe x4 (Fujitsu)
	InfiniBand HCA 1 x 40 Gbit/s PCIe Gen2 x8 (Mellanox)
	InfiniBand HCA 1 x 40 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 1 x 56 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 2 x 40 Gbit/s PCIe Gen2 x8 (Mellanox)
	InfiniBand HCA 2 x 40 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 2 x 56 Gbit/s PCIe Gen3 x8 (Mellanox)
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, PCIe x1, 2x DVI/VGA
Rack infrastructure	Rack Mount Kit
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks
	Cable Arm 2U for PRIMECENTER- and 3rd-party racks
Warranty	
Standard Warranty	3 years
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY RX300 S7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX300 S7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2012-09-28 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions